

SCD-5083RP



1/3 CMOS Colour/B&W Fixed Dome Camera w/ IR LED

- 1000 TV Lines
- Intelligent Video Analytics Function
- Coax Control Interface

Technical Specifications

Lens Focal Length	3 ~ 10 mm
IR Distance	30m
Image Sensor	1/3" Progressive Scan CMOS, 1.3 Megapixel
Pixels - Total	1312(H) x 1069(V)
Pixels - Effective	1305(H) x 1049(V)
Scanning System	Progressive
Sensitivity Colour	0.037 Lux @ F2.3
Sensitivity B/W	0.01 lux @ F1.2
S/N Ratio	>52dB (AGC off)
Video Outputs	BNC
OSD	Yes, multi language
Camera ID	Off / On
Col/B	On/Off/Auto
BLC Back Light	Off / User BLC / HLC / WDR
Number of Privacy Zones	24
Digital Noise Reduction (DNR)	SSNR IV (Off/On)
Motion Detection	On/Off
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Electronic Shutter	1-12,00 sec.
Digital Zoom	Off/1 ~ 16x
Shutter Speed	1 ~ 1/12.000 sec
Coaxial control	Pelco-C (Coaxitron®)
Lens Mount	C/CS mount
Lens Drive Type	Auto iris (DC)
Operating Temperature	-10°C ~ +55°C
Humidity	less than 90%, non condensing
Supply Voltage	12 Vdc, 24 Vac
Power Consumption (W)	6,0
Weight	0,550 kg - 0 lbs

SCD-5083RP

Dimensions

