

SCV-6023RP



1080p Analog HD Vandal-Resistant IR Dome Camera

- Compact Design
- Motion detection function
- Supports Easy Installation
- Support Dual Power
- Removable IR CUT Filter (ICR) for high IR sensitivity at night mode
- Day/Night feature with IR cut filter removable, for higher sensitivity and vibrant colors
- Weatherproof Outdoor Installation (IP66)

SCV-6023RP

Technical Specifications

Image Sensor	1/2.9" CMOS Full HD
Pixels - Total	2000(H) x 1121(V)
Pixels - Effective	1984(H) x 1105(V)
Sensitivity Colour	0.15Lux (F2.1)
Sensitivity B/W	0 Lux LED IR on
Max. IR Distance	20 m
Lens Focal Length	4 mm
MOD (Minimum Object Distance)	0.5m
S/N Ratio	>52 dB
Camera ID	15 character, On / Off
Col/B	Auto (ICR) / Color / B/W / External
WDR	D-WDR (Digital wide dynamic range)
Motion Detection	On/Off (4 Zones)
Lens Drive Type	Fixed
Digital Noise Reduction (DNR)	SSNR IV (Off/On)
Reverse	Off/ H-REV/ V-REV/ HV-REV
High Speed Shutter	Minimum / Maximum / Anti flicker (2-1/12.000sec)
BLC Back Light	BLC / HLC / off
White Balance	ATW, Manual, AWC, Indoor, Outdoor
Video Outputs	1x CVBS (1Vpp), BNC
Remote Control	Coaxial control
Reach	500m (75-5 coaxial cable)
Supply Voltage	12 VDC \pm 10%
Protection Rating	IK10, IP66
Operating Temperature	-30°C ~ +55°C
Humidity	less than 90%, non condensing
Material	Metal
Power Consumption (W)	4.2
Weight	0.560 kg - 1.23 lbs
Dimensions	Ø 137 mm - 5.39 In

SCV-6023RP



SCV-6023RP

Accessories



SBP-300B
Wall Mount Base



SBP-300PM
Pole mount adaptor



SBP-301HM2
Hanging mount adapter



SBP-300LM
Parapet mount adaptor



SBP-300CM
Ceiling Mount Adaptor



SBP-300WM1
Wall bracket



SBP-300WM
Wall bracket



SBP-300KM
Corner Mount Adaptor