

AXIS M3106-LVE Network Camera

Discreet, outdoor-ready 4 MP video surveillance with built-in IR illumination

AXIS M3106-LVE is an affordable, outdoor-ready fixed mini dome with a flat-faced design that suppresses reflections. Using WDR technology and IR illumination, it provides compact HDTV surveillance even in challenging light conditions or total darkness. The smart design allows for easy repainting, or using the optional black accessory casing to blend the camera into its environment. Axis' Zipstream technology reduces bandwidth and storage requirements. A variety of accessories are available for flexible and easy installation.

- > **Built-in IR illumination**
- > **Quad HD/4 MP video**
- > **Wide Dynamic Range (WDR)**
- > **Axis' Zipstream technology**
- > **Smart design for easy, flexible installation**



AXIS M3106-LVE Network Camera

| | | | |
|--|---|----------------------------------|---|
| Camera | | Casing | IP66-, NEMA 250 Type 4X, and IK08-rated, ASA polymer casing Encapsulated electronics, Captive screws (Torx 10) Color: White NCS S 1002-B For repainting instructions and impact on warranty, contact your Axis partner |
| Image sensor | 1/3" progressive scan RGB CMOS | Sustainability | PVC free |
| Lens | M12 mount, Fixed iris, Fixed focus 2.4 mm, F2.2 Horizontal field of view: 130° Vertical field of view: 73° | Memory | 512 MB RAM, 256 MB Flash |
| Day and night | Automatically removable infrared-cut filter | Power | Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical: 4.6 W, Max.: 9.3 W |
| Minimum illumination | Color: 0.3 lux at 50 IRE, F2.2 B/W: 0.06 lux at 50 IRE, F2.2 0 lux with IR illumination on | Connectors | RJ45 10BASE-T/100BASE-TX PoE |
| Shutter time | 1/31500 s to 1/5 s | IR illumination | Power-efficient, long-life 850 nm IR LEDs. Range of reach up to 15 m (50 ft) depending on scene |
| Camera angle adjustment | Pan: ±180° Tilt: 0° to 60° (0° = lens directed at a right angle to camera base) Rotation: ±95° Can be directed in any direction and see the wall/ceiling | Storage | Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations. |
| Video | | Operating conditions | -30°C to 50°C (-22 °F to 122 °F) Humidity 10–100% RH (condensing) |
| Video compression | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG | Storage conditions | -40 °C to 65 °C (-40 °F to 149 °F) |
| Resolutions | 2688x1520 to 320x240 | Approvals | EMC EN 55022 Class B, EN 55024, IEC 62471, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-78, IEC 60068-2-14, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK08, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60721-3-4 Class 4M3 Safety IEC/EN/UL 60950-22 |
| Frame rate | Up to 25/30 fps with power line frequency 50/60 Hz | Dimensions | Height: 94 mm (3.7 in) ø 101 mm (4.0 in) |
| Video streaming | Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth Axis' Zipstream technology in H.264 VBR/MBR H.264 | Weight | 370 g (0.81 lb) |
| Multi-view streaming | Up to 2 individually cropped out view areas in full frame rate | Included accessories | Installation Guide, Windows decoder 1-user license, Torx L-key, Connector guard |
| Pan/Tilt/Zoom | Digital PTZ | Optional accessories | AXIS T94B02D Pendant kit AXIS T94B01P Conduit Back Box AXIS T94B02M J-Box/Gang Box Plate Black casing Axis mounts AXIS Surveillance microSDXC™ Card AXIS T94 mounts for various installations AXIS Surveillance microSDXC™ Card |
| Image settings | Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, WDR, Rotation: 0°, 90°, 180°, 270° including Corridor Format, Text and image overlay, Privacy masks, Mirroring of images | Video management software | AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available |
| Network | | Languages | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese |
| Security | Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management | Warranty | Axis 3-year warranty and AXIS Extended Warranty option |
| Supported protocols | IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH | | |
| System integration | | | |
| Application Programming Interface | Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform. AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S. | | |
| Analytics | AXIS Video Motion Detection 3, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications | | |
| Event triggers | Analytics, Edge storage events | | |
| Event actions | Notification: email, HTTP, HTTPS and TCP and SNMP trap Video recording to edge storage Send video clip Pre- and post-alarm video buffering Overlay text | | |
| Data streaming | Event data | | |
| Built-in installation aids | Pixel counter | | |
| General | | | |

[Axis IP Cameras - Click Here](#)