

AXIS M5013 PTZ Dome Network Camera

Mini PTZ dome that gives the big picture

AXIS M5013 is an ultra-discreet, palm-sized, pan/tilt/zoom camera for remote indoor monitoring. The ceiling-mount camera enables flexible coverage over a 400 m² (4300 sq. ft) area, with a $\pm 180^\circ$ pan, 90° tilt and 3x digital zoom. It provides full frame rate video in SVGA resolution. It supports multiple H.264 and Motion JPEG video streams. The IP51 rating ensures protection against dust and dripping water, enabling the camera to operate even when a sprinkler system is activated. With a built-in microphone, AXIS M5013 enables users to listen to and record audio remotely. It also supports audio detection.

- > [Pan, tilt, zoom in an ultra-discreet design](#)
- > [SVGA and H.264](#)
- > [IP51-rated protection against dust and dripping water](#)
- > [Power over Ethernet \(IEEE 802.3af\)](#)
- > [Built-in microphone and audio detection](#)

AXIS M5013 PTZ Dome Network Camera

Camera		
Image sensor	Progressive scan RGB CMOS 1/4"	
Lens	3.6 mm, F1.8 Horizontal field of view: 45° Vertical field of view: 32°	
Minimum illumination	1.4 lux, F1.8	
Shutter time	1/25000 s to 1/6 s	
Pan/Tilt/Zoom	25 preset positions Pan: ±180°, 100°/s Tilt: 90°, 100°/s Zoom: 3x digital zoom	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Motion JPEG	
Resolutions	800x600 SVGA to 320x180	
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/MBR H.264	
Image settings	Manual shutter time, Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zones, Rotation, Backlight compensation, Fine tuning of behavior at low light, Text overlay	
Audio		
Audio streaming	One-way	
Audio compression	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	
Audio input	Built-in microphone	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S	
Analytics	Video motion detection, Audio detection Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line	
		Detection, AXIS Digital Autotracking and third-party applications.
Event triggers		Analytics, PTZ preset, Memory card full
Event actions		File upload: FTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP Go to PTZ preset; Video recording to edge storage Pre- and post-alarm video buffering
Built-in installation aids		Pixel counter
General		
Casing		IP51-rated plastic casing, clear dome
Sustainability		PVC free
Memory		256 MB RAM, 128 MB Flash
Power		Power over Ethernet 802.3af/802.3at Type 1 Class 3
Connectors		RJ45 10BASE-T/100BASE-TX PoE
Storage		Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations
Operating conditions		0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)
Storage conditions		-40 °C to 65 °C (-40 °F to 149 °F)
Approvals		EN 55022 Class A, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class A, VCCI Class B, RCM AS/NZS CISPR 22, KCC KN22 Class A, KN24, EN 60950-1 IEC/EN 60529 IP51
Dimensions		Ø130 x 58 mm (Ø5 1/8 x 2 1/4 in)
Weight		330 g (0.7 lb)
Included accessories		Drill template, Installation Guide, Windows decoder 1-user license AXIS M50 Clear Dome AXIS M50 Mounting Kit
Video management software		AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available
Languages		English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty		Axis 3-year warranty and AXIS Extended Warranty option