

AXIS Q1615-E Mk II Network Camera

High-speed excellence and outdoor-ready with i-CS lens

AXIS Q1615-E Mk II is ready for outdoor installations with protection against vandalism and tough weather. Thanks to an i-CS lens, the camera adjusts zoom and focus during remote setup, resulting in easy and quick installation. AXIS Q1615-E Mk II captures sharp video in up to 50/60 fps in HDTV 1080p and 100/120 fps in 720p HDTV. It delivers enhanced Lightfinder technology and WDR – Forensic Capture, optimizing video for forensic purposes in scenes with complex lighting. The camera features Scene Profiles with Forensic, Live and Traffic Overview profiles, allowing for automatic adjustment of image settings to meet specific surveillance needs.

- > **-40 °C to 60 °C (-40 °F to 140 °F)**
- > **Support for i-CS lens**
- > **Scene Profiles with automatically adjusted image settings**
- > **Electronic Image Stabilization**
- > **Axis' Zipstream technology**



AXIS Q1615-E Mk II Network Camera

Camera		Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email, send video clip Notification: email, HTTP, HTTPS and TCP Overlay text, Send SNMP Trap Video and audio recording to edge storage Pre- and post-alarm video buffering External output activation, day/night vision mode, play audio clip, status LED, WDR mode Defog mode, PTZ control
Image sensor	Progressive scan RGB CMOS 1/2.8"	Data streaming	Event data
Lens	Varifocal, IR corrected, CS-mount 2.8–8.5 mm, F1.2 Horizontal field of view 1080p: 72°–39° Vertical field of view 1080p: 38°–22° i-CS lens	Built-in installation aids	i-CS: Remote zoom and focus Other lens: Remote back focus Camera orientation aid Traffic wizard Pixel counter
Day and night	Automatically removable infrared-cut filter	General	
Minimum illumination	HDTV 1080p 25/30 fps: Color: 0.11 lux, B/W: 0.02 lux, at 50 IRE F1.2 HDTV 1080p 50/60 fps: Color 0.22 lux, B/W: 0.04 lux, at 50 IRE F1.2 HDTV 720p 100/120 fps: Color 0.44 lux, B/W: 0.09 lux, at 50 IRE F1.2	Casing	Enclosure: Metal (aluminium) Color: White NCS S 1002-B IP66- and NEMA 4X-rated, IK10 impact resistant aluminum enclosure
Shutter time	1/143000 to 2 s	Sustainability	PVC free
Pan/Tilt/Zoom	Digital PTZ, uploadable PTZ driver (Pelco D pre-installed)	Memory	512 MB RAM, 256 MB Flash
Video		Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3, max 12.95 W, typical 4.7 W High PoE, max 25.5 W
Video compression	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profile, Motion JPEG	Connectors	RJ45 10BASE-T/100BASE-TX PoE, 3.5 mm mic/line in, 3.5 mm line out RS485/RS422, Terminal block for two configurable inputs/outputs (12 V DC output, max load 50 mA)
Resolutions	HDTV 720p 100/120 fps (no WDR): 1280x720 to 160x90 HDTV 1080p 25/30 fps (WDR): 1920x1080 to 160x90 HDTV 1080p 50/60 fps (no WDR): 1920x1080 to 160x90	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS
Frame rate	Up to 100/120 fps (50/60 Hz) in 720p (no WDR)	Operating conditions	-30 °C to 60 °C (-22 °F to 140 °F) with PoE Down to -40 °C (-40 °F) with Axis High PoE Midspan, max 30 W Humidity 10–100% RH (condensing)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth Axis' Zipstream technology in H.264 VBR/MBR H.264	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, exposure zone, fine tuning of behavior at low light, text and image overlay, privacy mask, mirroring of images Rotation: auto, 0°, 90°, 180°, 270° WDR – forensic capture: Up to 120 dB depending on scene, barrel distortion correction, day/night shift level, electronic image stabilization, local contrast, defogging Scene profiles: forensic, live, traffic overview	Approvals	EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, IEC/EN/UL 60950-1 KCC KN32 Class A, KN35 EN 50121-4, IEC 62236-4, IEC/EN/UL 60950-22, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK10
Audio		Dimensions	161 x 142 x 404 mm (6 5/16 x 5 9/16 x 15 15/16 in)
Audio streaming	Two-way	Weight	3896 g (8.6 lb)
Audio compression	AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate	Included accessories	AXIS T94Q01A Wall Mount, Sunshield Connector kit, Resistorx™ T20 tool, Installation Guide, Windows decoder 1-user license
Audio input/output	External balanced/unbalanced microphone or line input, line output 24 bit AD/DA-conversion	Optional accessories	AXIS T91A47 Pole Mount, AXIS T94R01P Conduit Back Box, VT Corner Mount WCWA, VT Column Mount Ball Joint WFWCA, AXIS T98A16-VE Surveillance Cabinet, Axis optional lenses, AXIS T90B Illuminators, Axis network cable couplers, AXIS T8120 Midspan 15 W 1-port, AXIS T8133 Midspan 30 W 1-port, AXIS T8129 PoE Extender, AXIS Surveillance microSDXC™ Card 64 GB
Network		Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available
Security	Password protection, IP address filtering, HTTPS ⁹ encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Warranty	Axis 3-year warranty and AXIS Extended Warranty option
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S,		
Analytics	AXIS Video Motion Detection 3, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications,		
Event triggers	Analytics, Edge storage events, External input Shock detection Day/Night Mode, Live Stream Accessed, Network, Temperature, Manual Trigger, Virtual Inputs, PTZ Control, System Ready, Schedule		