

AXIS Q3615-VE Network Camera

Outstanding image quality with easy installation

Thanks to its 1/1.9" sensor and high-performance image processing, AXIS Q3615-VE supports Lightfinder and WDR - Forensic Capture with optimal image quality in difficult light conditions. It provides HDTV 1080p video at 30 fps with WDR, or up to 60 fps with WDR disabled. AXIS Q3615-VE offers a unique remote pan/tilt/roll/zoom (PTRZ) solution, easy conduit connection and cable management for minimized installation time. The PTRZ capability is also useful if the camera needs to be redirected. Robust and reliable, AXIS Q3615-VE is designed for harsh environments. Electronic image stabilization delivers steady images even during vibrations.

- > Exceptional video quality with 1/1.9" sensor
- > Lightfinder and WDR - Forensic Capture
- > HDTV 1080p up to 60 fps
- > Unique remote PTRZ capability for efficient installation
- > Axis' Zipstream technology



AXIS Q3615-VE Network Camera

Camera		Video recording to edge storage, Pre- and post-alarm video buffering, Zoom or digital PTZ preset, Overlay text, Send SNMP trap
Image sensor	Progressive scan RGB CMOS 1/1.9"	
Lens	Varifocal, 4.1–9 mm, F1.6 Horizontal field of view: 100°–46° Vertical field of view: 60°–29° Remote focus and zoom, P-Iris control, IR corrected	Data streaming Event data
Day and night	Automatically removable infrared-cut filter	Built-in installation aids Pan/tilt/roll: Designed to withstand at least 200 full cycles, Autoroll, Remote zoom, Remote focus, Pixel counter
Minimum illumination	HDTV 1080p 25/30 fps with WDR - forensic capture and Lightfinder: Color: 0.1 lux at 50 IRE, F1.6; B/W: 0.02 lux at 50 IRE, F1.6 HDTV 1080p 50/60 fps: Color: 0.2 lux at 50 IRE, F1.6; B/W: 0.03 lux at 50 IRE, F1.6	General
Shutter time	1/52500 s to 2 s	Casing IP66-, IP67-, IP6K9K- and NEMA 4X-rated, IK10 impact-resistant casing with polycarbonate dome, aluminum base and dehumidifying membrane Color: White NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.
Camera angle adjustment	Pan 370° Tilt +/- 81° Roll +/- 110°	Sustainability PVC free
Video		Memory 512 MB RAM, 256 MB Flash
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Power Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.5 W, max 10.4 W
Resolutions	1920x1200 to 160x90	Connectors RJ45 10BASE-T/100BASE-TX PoE
Frame rate	HDTV 1080p (1920x1080) with WDR: 25/30 fps with power line frequency 50/60 Hz HDTV 1080p (1920x1080) without WDR: 50/60 fps with power line frequency 50/60 Hz WUXGA (1920x1200) without WDR: 25/30 fps with power line frequency 50/60 Hz	Storage Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis' Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Operating conditions -40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)
Multi-view streaming	2 individually cropped out view areas	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zone, Noise reduction, Fine tuning of behavior at low light, Rotation: 0°, 90°, 180°, 270° including Corridor Format, Text and image overlay, Privacy mask, Mirroring of images, Electronic image stabilization, Barrel distortion correction WDR - forensic capture: Up to 120 dB depending on scene	Approvals EMC EN 55022 Class B, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 60950-22 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/67, ISO 20653 IP6K9K, NEMA 250 Type 4X, IEC/EN 62262 IK10
Pan/Tilt/Zoom	2.2x optical zoom and 2x digital zoom Digital PTZ Optical zoom and digital PTZ preset positions	Dimensions Depth: 166 mm (6 9/16 in) Depth with weather shield: 224 mm (8 13/16 in) ø 198 mm (7 13/16 in)
Network		Weight 2.3 kg (5.1 lb) with weather shield
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Included accessories AXIS Connector Guard A, Safety hook wire, Installation Guide, Windows decoder 1-user license, Resistorx [®] L-key, Weather shield, Mounting bracket, Drill template, Cable gasket, Axis U-shape conduit adapter
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Optional accessories AXIS T94V01L Recessed Mount, AXIS T94V01D Pendant Kit, AXIS T98A17-VE Cabinets, Axis Pole Mounts, Axis Ceiling Mounts, Axis Wall Mounts, AXIS T90B Illuminators, AXIS ACI Conduit Adapter 3/4" NPS, AXIS Q36-VE Smoked Dome, AXIS Surveillance microSDXC [™] Card
System integration		Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available.
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S,	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Analytics	AXIS Video Motion Detection 3, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender, AXIS Digital Autotracking and third-party applications	Warranty Axis 3-year warranty and AXIS Extended Warranty option
Event triggers	Analytics, Edge storage events, Shock detection	
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP	