

# AXIS P5415-E PTZ Dome Network Camera

## Intelligent direct drive HDTV 1080p PTZ dome

AXIS P5415-E is an HDTV 1080p PTZ dome with 18x optical zoom. Designed to blend in with a building, AXIS P5415-E mounts directly on the wall with a built-in bracket for ease of installation. When mounted on the corner of a building, it enables 270° pan for wide area coverage. AXIS P5415-E features a direct drive pan/tilt system with no belts or gears, enabling reliable, low-maintenance mechanics. The sunshield can be easily removed and repainted to match the wall color. A hidden junction box supports two-way audio, a memory card slot, four configurable input/output ports, 24 V DC and Power over Ethernet.

- > [Outdoor wall-mount design for easy installation](#)
- > [Repaintable, integrated sunshield](#)
- > [Durable, low maintenance mechanics](#)
- > [HDTV 1080p and 18x optical zoom](#)
- > [Two-way audio & input/output ports](#)



# AXIS P5415-E PTZ Dome Network Camera

<b>Models</b>	AXIS P5415-E 50 Hz AXIS P5415-E 60 Hz	PTZ: PTZ preset, start/stop guard tour File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP	
<b>Camera</b>			
<b>Image sensor</b>	Progressive scan RGB CMOS 1/2.8"	<b>Data streaming</b> Event data	
<b>Lens</b>	4.7–84.6 mm, F1.6–2.8 Horizontal angle of view: 59°–4° Vertical angle of view: 35°–2° Autofocus	<b>Built-in installation aids</b> Pixel counter	
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>General</b>	
<b>Minimum illumination</b>	Color: 0.5 lux at 30 IRE F1.6 B/W: 0.04 lux at 30 IRE F1.6	<b>Casing</b> IP66- and NEMA 4X-rated, IK07 impact-resistance Metal casing (aluminum), clear dome (PC), sunshield (ASA)	
<b>Shutter time</b>	2 s to 1/28000 s	<b>Sustainability</b> PVC free	
<b>Pan/Tilt/Zoom</b>	18x optical zoom and 12x digital zoom, total 216x zoom 100 preset positions, Limited guard tour, Control queue, Focus window, On-screen directional indicator Pan: ± 135° <sup>a</sup> 0.2°–400°/s Tilt: 0°–90° 0.2°–400°/s	<b>Memory</b> 256 MB RAM, 128 MB Flash	
<b>Video</b>			
<b>Video compression</b>	H.264 Main and Baseline Profiles (MPEG-4 Part 10/AVC) Motion JPEG	<b>Power</b> Axis PoE+ midspan 1-port: 100–240 V AC, max 37 W IEEE 802.3at Type 2 Class 4 <b>Multi-connector cable:</b> 24 V DC, max 16 W PoE+ midspan and power supply not included.	
<b>Resolutions</b>	1920x1080 to 160x90	<b>Connectors</b> RJ45 for 10BASE-T/100BASE-TX PoE Terminal blocks for DC input, 4 configurable alarm inputs/outputs, Mic in/Line in, Line out	
<b>Frame rate</b>	Up to 25/30 fps (50/60 Hz) in all resolutions	<b>Storage</b> Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations	
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264	<b>Operating conditions</b> -20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–100% RH (condensing)	
<b>Image settings</b>	Wide dynamic range, Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zones, Backlight compensation, Fine tuning of behavior at low light, Text and image overlay, 20 individual 3D privacy masks	<b>Storage conditions</b> -40 °C to 65 °C (-40 °F to 149 °F) Humidity 10–80% RH (non-condensing)	
<b>Audio</b>			
<b>Audio streaming</b>	Two-way	<b>Approvals</b> EN 50121-4, IEC 62236-4: 2008, EN 50581, EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78, IEC 60529 IP66, NEMA 250 Type 4X, IEC 62262 Class IK07, ISO 4892-2	
<b>Audio compression</b>	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	<b>Dimensions</b> 279 x 193 x 239 (11 x 7 5/8 x 9 7/16 in)	
<b>Audio input/output</b>	External microphone or line input, and line output	<b>Weight</b> 3.5 kg (7.7 lb.)	
<b>Network</b>			
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>b</sup> encryption, IEEE 802.1X <sup>b</sup> network access control, Digest authentication, User access log, Centralized Certificate Management	<b>Included accessories</b> Installation Guide, AVHS Authentication key, Windows decoder 1-user license AXIS ACI Conduit Adapter 3/4" U-Shape 30 mm Weather Cover	
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>b</sup> , SSL/TLS <sup>b</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCP	<b>Optional accessories</b> AXIS P54 Smoked Dome AXIS T8133 Midspan 30 W 1-port AXIS T8415 Wireless Installation Tool AXIS T94P01B Corner Bracket AXIS T98A19-VE Surveillance Cabinet	
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform. AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S.	<b>Video management software</b> AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development	
<b>Analytics</b>	Video motion detection, Audio detection, Advanced Gatekeeper Support for AXIS Camera Application Platform enabling installation of third-party applications.	<b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
<b>Event triggers</b>	Detectors: live stream accessed, video motion detection Hardware: network, temperature, fan Input Signal: manual trigger, virtual inputs PTZ: error, moving, preset reached, ready Storage: disruption, recording System: system ready Time: recurrence, use schedule	<b>Warranty</b> Axis 3-year warranty and AXIS Extended Warranty option	
<b>Event actions</b>	Day/night mode, overlay text, external output activation, video recording to edge storage, pre- and post-alarm video buffering, play audio clip, send SNMP trap		