

# AXIS P5514-E PTZ Dome Network Camera

Cost-effective, outdoor-ready PTZ dome camera

AXIS P5514-E is a compact pan/tilt/zoom camera that enables users to pan 360° for overview surveillance and zoom 12x with autofocus for detailed views. It provides HDTV resolution up to 720p at 50/60 fps frame rate. Day/night functionality ensures maintained image quality even in low light conditions. The camera ensures protection against dust, rain, snow, ice, and corrosion. It can operate in temperatures from -20 °C to 50 °C (-4 °F to 122 °F). The SD/SDHC slot enables local video storage.

- > **12x optical zoom**
- > **360° pan with Auto-flip**
- > **Axis' Zipstream technology**
- > **Protection against dust, rain, and snow**
- > **Easy installation including Power over Ethernet**



# AXIS P5514-E PTZ Dome Network Camera

<b>Camera</b>	
<b>Image sensor</b>	1/2.3" progressive scan CMOS
<b>Lens</b>	3.8–42.9 mm, F1.4–2.1 Horizontal field of view: 59.2°–5.2° Vertical field of view: 33.3°–3.1° Autofocus, Auto-iris
<b>Day and night</b>	Automatically removable infrared-cut filter
<b>Minimum illumination</b>	Color: 0.7 lux at 30 IRE F1.4 B/W: 0.08 lux at 30 IRE F1.4
<b>Shutter time</b>	1/8000 s to 1/30 s at 60 Hz 1/8000 s to 1/25 s at 50 Hz
<b>Pan/Tilt/Zoom</b>	Pan: 360° (with auto-flip), 1.8°–100°/s Tilt: 180°, 1.8°–100°/s 12x optical zoom, 10x digital zoom, total 120x zoom E-flip, Auto-flip, 100 preset positions, Limited guard tour, Control queue
<b>Video</b>	
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) – Baseline, Main and High Profiles Motion JPEG
<b>Resolutions</b>	1280x720 to 320x180
<b>Frame rate</b>	Up to 60/50 fps in all resolutions
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis' Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264
<b>Image settings</b>	Compression, Brightness, Sharpness, White balance, Exposure control, Backlight compensation, WDR – Dynamic Contrast, Fine tuning of behavior at low light, Rotation, Text and image overlay, Image freeze on PTZ
<b>Network</b>	
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management
<b>Supported protocols</b>	IPv4/IPv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMP v1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH
<b>System integration</b>	
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile G,
<b>Analytics</b>	Video motion detection, Advanced Gatekeeper Support for AXIS Camera Application Platform enabling installation of third-party applications.
<b>Event triggers</b>	Detectors: Live stream accessed, Video motion detection Hardware: Fan, Network, Temperature Input Signal: Digital Input Port, Manual trigger, Virtual inputs PTZ: Error, Moving, Preset reached, Ready Storage: Disruption, Recording System: System ready Time: Recurrence, Use schedule

<b>Event actions</b>	Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap PTZ: PTZ preset, start/stop guard tour File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP
<b>Data streaming</b>	Event data
<b>Built-in installation aids</b>	Pixel counter
<b>General</b>	
<b>Casing</b>	IP66-, NEMA 4X- and IK07-rated Aluminum and plastic casing, polycarbonate (PC) dome, sunshield (PC/ASA)
<b>Memory</b>	512 MB RAM, 256 MB Flash
<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Camera consumption: typical: 6.9 W, max 12.95 W (PoE midspan and power supply not included)
<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE IP66-rated RJ45 connector kit included
<b>Storage</b>	Support for SD/SDHC/SDXC card (not included) Support for recording to dedicated network-attached storage (NAS)
<b>Operating conditions</b>	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–100% RH (condensing)
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Approvals</b>	EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN22 Class A, KN24, IEC/EN/UL 60950-1, IEC 60068-2, IEC 60721-4-3 Class 3K3, 3M3 +B38 IEC/EN/UL 60950-22
<b>Weight</b>	1.3 kg (2.9 lb) Drop-ceiling mount (Plenum rated): 1.2 kg (2.6 lb)
<b>Included accessories</b>	Sunshield, RJ45 Push-pull Connector (IP66) Installation Guide, Windows decoder 1-user license
<b>Optional accessories</b>	T91 Mounting Accessories, AXIS T94A03L Recessed Mount Kit
<b>Video management software</b>	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option,