

AXIS P5514 PTZ Dome Network Camera

Cost-effective, indoor PTZ dome camera

AXIS P5514 is a compact pan/tilt/zoom camera that enables users to pan 360° for overview surveillance and zoom 12x with autofocus for detailed views. It provides HDTV resolution up to 720p at 50/60 fps frame rate. Day/night functionality ensures maintained image quality even in low light conditions. With an optional multi-connector cable, AXIS P5514 supports two-way audio, audio detection, I/O ports for external devices, and AC/DC power. The camera ensures protection against dust and dripping water, allowing it to operate even when a sprinkler system is activated. The SD/SDHC slot enables local video storage.

- > [12x optical zoom](#)
- > [360° pan with Auto-flip](#)
- > [Axis' Zipstream technology](#)
- > [Protection against dust and water](#)
- > [Easy installation including Power over Ethernet](#)



AXIS P5514 PTZ Dome Network Camera

Camera	
Image sensor	1/2.3" progressive scan CMOS
Lens	3.8–42.9 mm, F1.4–2.1 Horizontal field of view: 59.2°–5.2° Vertical field of view: 33.3°–3.1° Autofocus, Auto-iris
Day and night	Automatically removable infrared-cut filter
Minimum illumination	Color: 0.7 lux at 30 IRE F1.4 B/W: 0.08 lux at 30 IRE F1.4
Shutter time	1/8000 s to 1/30 s at 60 Hz 1/8000 s to 1/25 s at 50 Hz
Pan/Tilt/Zoom	Pan: 360° (with auto-flip), 1.8°–100°/s Tilt: 180°, 1.8°–100°/s 12x optical zoom, 10x digital zoom, total 120x zoom E-flip, Auto-flip, 100 preset positions, Limited guard tour, Control queue
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) – Baseline, Main and High Profiles Motion JPEG
Resolutions	1280x720 to 320x180
Frame rate	Up to 60/50 fps in all resolutions
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis' Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264
Image settings	Compression, Brightness, Sharpness, White balance, Exposure control, Backlight compensation, WDR – Dynamic Contrast, Fine tuning of behavior at low light, Rotation, Text and image overlay, Image freeze on PTZ
Audio	
Audio streaming	Two-way, full duplex
Audio compression	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate
Audio input/output	Requires multi-connector cable (sold separately) for external microphone or line input, and line output
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile G
Analytics	Audio detection Video motion detection, Advanced Gatekeeper Support for AXIS Camera Application Platform enabling installation of third-party applications
Event triggers	Detectors: Live stream accessed, Video motion detection, Audio detection Hardware: Fan, Network, Temperature Input Signal: Digital Input Port, Manual trigger, Virtual inputs PTZ: Error, Moving, Preset reached, Ready

	Storage: Disruption, Recording System: System ready Time: Recurrence, Use schedule
Event actions	Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap PTZ: PTZ preset, start/stop guard tour File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP External output activation, play audio clip
Data streaming	Event data
Built-in installation aids	Pixel counter
General	
Casing	IP51-rated Aluminum and plastic casing, polycarbonate (PC) dome
Memory	512 MB RAM, 256 MB Flash
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Camera consumption: typical 6.3 W, max 12.95 W Multi-connector cable: 20–24 V AC, typical 11 VA, max 22 VA 20–28 V DC, typical 6 W, max 13.5 W (PoE midspan and power supply not included)
Connectors	RJ45 10BASE-T/100BASE-TX PoE Multi-connector (cable not included) for AC/DC power, 4 configurable alarm inputs/outputs, mic in, line mono input, line mono output to active speaker
Storage	Support for SD/SDHC/SDXC card (not included) Support for recording to dedicated network-attached storage (NAS)
Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 15–85% RH (non-condensing)
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F)
Approvals	EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN22 Class A, KN24, IEC/EN/JUL 60950-1, IEC 60068-2, IEC 60721-4-3 Class 3K3, 3M3 +B38 EN 61000-6-2
Weight	1.1 kg (2.4 lb)
Included accessories	Smoked dome cover, Mounting kit for hard and drop ceilings Installation Guide, Windows decoder 1-user license
Optional accessories	T91 Mounting Accessories, AXIS T94A03L Recessed Mount Kit Multi-connector cable for AC/DC power, I/Os and audio
Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	Axis 3-year warranty and AXIS Extended Warranty option