

CP- VNC-T21FR5-VM

2 MP Full HD Array Bullet Camera - 50Mtr.

INDIGO



Main Features

- 1/2.9" 2MP PS CMOS Image Sensor
- 1080P: Max. 30 fps , 720P: Max. 30 fps , D1: Max. 8 fps
- H.265, H.264, MJPEG Triple-stream Encoding
- Day/Night (ICR), Corridor mode, 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 2.8~12 mm Varifocal Lens
- IR Range of 50 Mtrs, IP67, SD Card, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS



InstaStream

CE FCC RoHS COMPLIANT

CP- VNC-T21FR5-VM

2 MP Full HD Array Bullet Camera - 50Mtr.



Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control(AGC)
 Video Compression
 S/N Ratio
 Video Streaming
 Resolution
 Frame Rate
 Privacy Mask
 ICR
 ROI
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out

 Protocol

 Smart Detection

 Ethernet
 IR
 OSD
 Micro SD
 Audio
 Operating Temperature
 Humidity
 Power Source
 Power Consumption

Specification

1/2.9" 2MP Progressive scan CMOS
 Colour: 0.06 Lux (F1.4, AGC ON) 0 Lux with IR
 Auto/Manual, 1/6~1/100000s
 Auto/Manual
 2.8~12 mm Varifocal Lens
 Auto/Manual
 H.265, H.264, MJPEG
 >52dB
 Triple
 1920x1080
 1080P (1920 x 1080): Max. 30 fps , 720P (1280 x 720): Max. 30 fps , D1 (720 x 576): Max.8 fps
 Up to 8 areas
 IR-cut filter with auto switch (ICR)
 Supports
 impedance 35 kΩ; amplitude 2 V [p-p]
 impedance 600 Ω; amplitude 2 V [p-p]
 G.711
 1 channel
 1 channel

 IPv4, IGMP, ICMP, ARP, TCP, UDP, L2TP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, ONVIF, API

 Intrusion, crossing line, Motion detection, Audio detection, Face detection, Defocus, Scene Change, People counting

 1 RJ45 10M/100M Base-TX Ethernet
 Array Range of 50 Mtr.
 Up to 8 OSDs
 Micro SD, up to 128 GB
 Two-way audio Supported
 -35°C ~ +60°C (-31°F ~ 140°F)
 ≤ 95% RH (non-condensing)
 12 V DC, or PoE (IEEE802.3 af)
 Max 8W



CP- VNC-T21FR5-VM

2 MP Full HD Array Bullet Camera - 50Mtr.



Feature

Weatherproof Standard

Dimension

Weight

Specification

IP67

253.4mm x 86mm x 71.7 mm (9.98" x 3.4" x 2.8")

0.58kg